

TLB型稠油泵性能参数

规格型号 specification type	额定流量 rated flow (m <sup>3</sup> /h)	轴功率 axle power (KW)	配带电动机 fitting motor		进出口径 calibre for inlet & outlet (mm)	泵效率 Pump efficiency (%)	吸上高度 drawing up height (m)	额定工作压力 rated working pressure (MPa)	工作温度 working temperature (°C)	泵转数 Pump revolution (r/min)	重量 weight (kg)
			电机型号 motor type	功率 power (KW)							
TLB-5/0.6	5	1.25	Y/YB112M-6	2.2	50	61	5	0.6	≤150 (≤300)	302	660
TLB-8/0.6	8	2	Y/YB132S-6	3.0	65	61				302	730
TLB-10/0.6	10	2.5	Y/YB132S-6	3.0	80	64				167	925
TLB-12.5/0.6	12.5	3.19	Y/YB132M <sub>1</sub> -6	4.0	80	64				167	930
TLB-16/0.6	16	4.02	Y/YB132M <sub>2</sub> -6	5.5	80	64				209	1000
TLB-20/0.6	20	4.88	Y/YB160M-6	7.5	100	64				167	1570
TLB-25/0.6	25	6.28	Y/YB160L-6	11	100	67				167	1600
TLB-31.5/0.6	31.5	7.69	Y/YB160L-6	11	150	67				167	1650
TLB-36/0.6	36	9.05	Y/YB160L-6	11	150	67				167	1680
TLB-40/0.6	40	9.34	Y/YB180L-6	15	150	70				167	1740
TLB-50/0.6	50	12.5	Y/YB200L <sub>1</sub> -6	18.5	200	70				167	2200
TLB-63/0.6	63	15.84	Y/YB200L <sub>2</sub> -6	22	200	70				167	2350
TLB-80/0.6	80	20.12	Y/YB225-6	30	200	70				167	2850
TLB-100/0.6	100	25.15	Y/YB250M-6	37	200	73				167	2900
TLB-125/0.6	125	31.4	Y/YB280S-6	45	200	73				167	3050
TLB-160/0.6	160	40.2	Y/YB280M-6	55	300	73				154	4950
TLB-200/0.6	200	50.3	Y/YB315S-6	75	300	73				154	5300
TLB-250/0.6	250	62.8	Y/YB315M-6	90	300	73				154	5500
TLB-300/0.6	300	76.4	Y/YB315M-6	90	300	73				154	5850
TLB-5/1.0	5	2.09	Y/YB132S-6	3.0	50	61				5	1.0
TLB-8/1.0	8	3.35	Y/YB132M <sub>1</sub> -6	4.0	65	61	302	750			
TLB-10/1.0	10	4.19	Y/YB132M <sub>2</sub> -6	5.5	80	61	167	980			
TLB-12.5/1.0	12.5	4.86	Y/YB132M <sub>2</sub> -6	5.5	80	64	167	1000			
TLB-16/1.0	16	6.7	Y/YB160M-6	7.5	100	64	209	1100			
TLB-20/1.0	20	8.51	Y/YB160L-6	11	100	64	167	1680			
TLB-25/1.0	25	10.41	Y/YB180L-6	15	150	67	167	1700			
TLB-31.5/1.0	31.5	12.84	Y/YB180L-6	15	150	67	167	1730			
TLB-36/1.0	36	15.09	Y/YB200L <sub>1</sub> -6	18.5	150	67	167	1750			
TLB-40/1.0	40	16.26	Y/YB200L <sub>1</sub> -6	18.5	200	67	167	1850			
TLB-50/1.0	50	19.46	Y/YB200L <sub>2</sub> -6	22	200	70	167	2320			
TLB-63/1.0	63	26.4	Y/YB225M-6	30	200	70	167	2450			
TLB-80/1.0	80	33.5	Y/YB250M-6	37	200	70	167	2950			
TLB-100/1.0	100	41.9	Y/YB280S-6	45	200	73	167	3600			
TLB-125/1.0	125	52.3	Y/YB280M-6	55	200	73	167	3680			
TLB-160/1.0	160	67.07	Y/YB315S-6	75	300	73	154	5100			
TLB-200/1.0	200	83.85	Y/YB315M-6	90	300	73	154	5350			
TLB-250/1.0	250	104.7	Y/YB315L <sub>1</sub> -6	110	300	73	154	5650			
TLB-300/1.0	300	125.6	Y/YB315L <sub>2</sub> -6	132	300	73	154	5850			
TLB-5/1.6	5	3.35	Y/YB132M-6	5.5	50	59	5	1.6	≤150 (≤300)		
TLB-8/1.6	8	5.35	Y/YB160M-6	7.5	50	59				167	1020
TLB-10/1.6	10	6.7	Y/YB160M-6	7.5	80	59				209	1000
TLB-12.5/1.6	12.5	8.79	Y/YB160L-6	11	80	62				209	1050
TLB-16/1.6	16	11.25	Y/YB180L-6	15	80	62				209	1200
TLB-20/1.6	20	14.06	Y/YB180L-6	15	100	62				167	1800
TLB-25/1.6	25	16.76	Y/YB200L <sub>1</sub> -6	18.5	100	65				167	1900
TLB-31.5/1.6	31.5	21.12	Y/YB200L <sub>2</sub> -6	22	150	65				167	2000
TLB-36/1.6	36	24.15	Y/YB225M-6	30	150	65	167	2100			

TLB型稠油泵性能参数

规格型号 specification type	额定流量 rated flow (m <sup>3</sup> /h)	轴功率 axle power (KW)	配带电动机 fitting motor		进出口径 calibre for inlet & outlet (mm)	泵效率 Pump efficiency (%)	吸上高度 drawing up height (m)	额定工作压力 rated working pressure (MPa)	工作温度 working temperature (°C)	泵转数 Pump revolution (r/min)	重量 weight (kg)			
			电机型号 motor type	功率 power (KW)										
TLB-40/1.6	40	26.82	Y/YB225M-6	30	150	65	5	1.6	≤150 (≤300)	167	2600			
TLB-50/1.6	50	33.53	Y/YB250M-6	37	200	68				167	3300			
TLB-63/1.6	63	42.25	Y/YB280S-6	45	200	68				167	3500			
TLB-80/1.6	80	53.65	Y/YB280M-6	55	200	68				167	4300			
TLB-100/1.6	100	67.07	Y/YB315S-6	75	200	71				167	4900			
TLB-125/1.6	125	83.83	Y/YB315M-6	90	200	71				167	5000			
TLB-160/1.6	160	107.3	Y/YB315L <sub>1</sub> -6	110	300	71				154	5340			
TLB-200/1.6	200	122.8	Y/YB315L <sub>2</sub> -6	132	300	71				167	5560			
TLB-5/2.5	5	5.67	Y/YB160M-6	7.5	50	57				5	2.5	≤150 (≤300)	167	1020
TLB-8/2.5	8	9.08	Y/YB160L-6	11	50	57	167	1050						
TLB-10/2.5	10	11.35	Y/YB180L-6	15	80	57	209	1250						
TLB-12.5/2.5	12.5	14.43	Y/YB180L-6	15	80	59	209	1300						
TLB-16/2.5	16	18.16	Y/YB200L <sub>1</sub> -6	18.5	80	59	209	1500						
TLB-20/2.5	20	23.1	Y/YB225M-6	30	100	59	167	2215						
TLB-25/2.5	25	28.39	Y/YB225M-6	30	100	63	167	2400						
TLB-31.5/2.5	31.5	34.1	Y/YB250M-6	37	150	63	167	2500						
TLB-36/2.5	36	40.87	Y/YB280S-6	45	150	63	167	2620						
TLB-40/2.5	40	43.25	Y/YB280S-6	45	150	63	167	3550						
TLB-50/2.5	50	56.76	Y/YB315S-6	75	200	66	167	3700						
TLB-63/2.5	63	71.5	Y/YB315S-6	75	200	66	167	3900						
TLB-80/2.5	80	90.8	Y/YB315L <sub>1</sub> -6	110	200	66	167	4600						
TLB-100/2.5	100	113.5	Y/YB315L <sub>2</sub> -6	132	200	69	167	4850						
TLB-5/3.2	5	7.65	Y/YB160L-6	11	50	57	5	3.2	≤150 (≤300)				167	1050
TLB-8/3.2	8	12.24	Y/YB180L-6	15	50	57							209	1100
TLB-10/3.2	10	15.3	Y/YB200L <sub>1</sub> -6	18.5	80	57							209	1320
TLB-12.5/3.2	12.5	17.3	Y/YB200L <sub>1</sub> -6	18.5	80	59							209	1560
TLB-16/3.2	16	23.65	Y/YB225M-6	30	80	59				209	2100			
TLB-20/3.2	20	27.68	Y/YB225M-6	30	100	59				167	2250			
TLB-25/3.2	25	34.6	Y/YB250M-6	37	100	63				167	2316			
TLB-31.5/3.2	31.5	43.6	Y/YB280M-6	55	150	63				167	2520			
TLB-36/3.2	36	52.32	Y/YB280M-6	55	150	63				167	2600			
TLB-40/3.2	40	55.36	Y/YB315S-6	75	150	63				167	3770			
TLB-50/3.2	50	72.66	Y/YB315S-6	75	200	66				167	3770			
TLB-63/3.2	63	91.55	Y/YB315L <sub>1</sub> -6	110	200	66				167	4250			
TLB-80/3.2	80	116.25	Y/YB315L <sub>2</sub> -6	132	200	66				167	4980			
TLB-5/4.0	5	11.08	Y/YB180L-6	15	50	57				5	4.0	≤150 (≤300)	167	1100
TLB-8/4.0	8	15.5	Y/YB200L <sub>1</sub> -6	18.5	50	57							209	1200
TLB-10/4.0	10	18.16	Y/YB200L <sub>2</sub> -6	22	80	57	167	1500						
TLB-12.5/4.0	12.5	23.1	Y/YB250M-6	37	80	59	167	1800						
TLB-16/4.0	16	29.06	Y/YB250M-6	37	200	59	154	3770						
TLB-20/4.0	20	36.9	Y/YB280S-6	45	200	59	167	2300						
TLB-25/4.0	25	41.4	Y/YB280M-6	45	200	63	167	2850						
TLB-31.5/4.0	31.5	52.5	Y/YB280M-6	55	200	63	167	2900						
TLB-36/4.0	36	65.4	Y/YB315S-6	75	200	63	167	3100						
TLB-40/4.0	40	69.2	Y/YB315S-6	75	200	63	167	3650						
TLB-50/4.0	50	82.57	Y/YB315M-6	90	200	66	167	3770						
TLB-63/4.0	63	104.4	Y/YB315L <sub>1</sub> -6	110	200	66	167	4360						